## NSN 5340-00-884-8594

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-884-8594

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.720 inches and 0.780 inches

Second Leg Length:

Between 1.280 inches and 1.340 inches

Second Leg Width:

Between 3.070 inches and 3.130 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Hole Diameter:

0.281 inches

Second Leg Distance Between Hole Centers Along Width:

Between 2.230 inches and 2.250 inches

Second Leg Distance Between Hole Centers Along Length:

0.270 mils and 0.290 centimeters

**Second Leg Distance From Edge To Hole Center Along Width:** 

Between 0.600 inches and 0.620 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

**Center Section Height:** 

Between 0.667 inches and 0.699 inches

**Center Section Width:** 

Between 3.070 inches and 3.130 inches

**Center Section Thickness:** 

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 3.070 inches and 3.130 inches

First Leg Corner Radius:

Between 0.240 inches and 0.260 inches

First Leg Distance Between Hole Centers Along Width:

Between 2.590 inches and 2.610 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Style:

Corner radius

## NSN 5340-00-884-8594

Double Angle Bracket - Page 2 of 2



First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Corner radius
Second Leg Hole Arrangement Style:
Two holes
Material:
Steel comp 321
Material Specification:
Ams 5510 assn standard single material response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Δ0/12=0