NSN 5340-00-884-8594

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-884-8594

Fabrication Method (non-core): Machined First Leg Length: Between 0.720 inches and 0.780 inches Second Leg Length: Between 1.280 inches and 1.340 inches Second Leg Width: Between 3.070 inches and 3.130 inches First Leg Hole Diameter: 0.281 inches Second Leg Hole Diameter: 0.281 inches Second Leg Distance Between Hole Centers Along Width: Between 2.230 inches and 2.250 inches Second Leg Distance Between Hole Centers Along Length: 0.270 mils and 0.290 centimeters Second Leg Distance From Edge To Hole Center Along Width: Between 0.600 inches and 0.620 inches Second Leg Distance From Edge To Hole Center Along Length: Between 0.240 inches and 0.260 inches First Leg Thickness: Between 0.057 inches and 0.069 inches Second Leg Thickness: Between 0.057 inches and 0.069 inches **Center Section Height:** Between 0.667 inches and 0.699 inches **Center Section Width:** Between 3.070 inches and 3.130 inches **Center Section Thickness:** Between 0.057 inches and 0.069 inches First Leg Width: Between 3.070 inches and 3.130 inches First Leg Corner Radius: Between 0.240 inches and 0.260 inches First Leg Distance Between Hole Centers Along Width: Between 2.590 inches and 2.610 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.240 inches and 0.260 inches First Leg Distance From Edge To Hole Center Along Length: Between 0.240 inches and 0.260 inches First Leg Style: Corner radius

NSN 5340-00-884-8594

Double Angle Bracket - Page 2 of 2



First Leg Hole Arrangement Style: Two holes Second Leg Style: Corner radius Second Leg Hole Arrangement Style: Two holes Material: Steel comp 321 **Material Specification:** Ams 5510 assn standard single material response Style Designator: Double angle Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A042a0