

View Online at <https://aerobasegroup.com/nsn/5340-00-884-8594>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.720 inches and 0.780 inches

Second Leg Length:

Between 1.280 inches and 1.340 inches

Second Leg Width:

Between 3.070 inches and 3.130 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Hole Diameter:

0.281 inches

Second Leg Distance Between Hole Centers Along Width:

Between 2.230 inches and 2.250 inches

Second Leg Distance Between Hole Centers Along Length:

0.270 mils and 0.290 centimeters

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.600 inches and 0.620 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

Center Section Height:

Between 0.667 inches and 0.699 inches

Center Section Width:

Between 3.070 inches and 3.130 inches

Center Section Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 3.070 inches and 3.130 inches

First Leg Corner Radius:

Between 0.240 inches and 0.260 inches

First Leg Distance Between Hole Centers Along Width:

Between 2.590 inches and 2.610 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0