

View Online at <https://aerobasegroup.com/nsn/5340-00-886-1275>

First Leg Length:

0.440 inches

Second Leg Length:

1.672 inches

Second Leg Width:

0.750 inches

First Leg Hole Diameter:

0.086 inches

Second Leg Hole Diameter:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.375 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.097 inches

Second Leg Distance Between First And Second Hole Centers Along Length:

0.363 inches

Second Leg Distance Between Second And Third Hole Centers Along Length:

0.960 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

First Leg Width:

1.340 inches

First Leg Distance Between Hole Centers Along Width:

0.937 inches

First Leg Distance From Edge To Hole Center Along Width:

0.201 inches

First Leg Distance From Edge To Hole Center Along Length:

0.184 inches

Second Leg End Radius:

0.375 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

First hole 0.193 diameter and 3 holes 0.156 diameter 0.843 from c/l first hole ist and 3rd small holes0.141 c/l 2nd

Heat Treatment:

H-32 strain hardened

Material:

Aluminum alloy 5052

Surface Treatment:

Oxide film

Surface Treatment Specification:

Mil-c-5541 type 1 gr c cl 1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.