## NSN 5340-00-886-2189

Access Cover - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-00-886-2189

Cross Sectional Shape:
Flat
Hole Diameter:
Between 0.281 inches and 0.288 inches
Width:
8.300 inches
Edge Shape:
Oval, multi holes
Length:
12.300 inches
Hole Quantity Along Length:
6
Hole Quantity Along Width:
8
Body Thickness:
0.187 inches
Securing Device Type:
Threaded fastener
Mounting Opening Shape Style:
Unthreaded hole
Material:
Material: Aluminum alloy 7075
Aluminum alloy 7075
Aluminum alloy 7075  Material Specification:
Aluminum alloy 7075  Material Specification:  Qq-a-250/12, t6 federal specification single material response
Aluminum alloy 7075  Material Specification:  Qq-a-250/12, t6 federal specification single material response  Surface Treatment:
Aluminum alloy 7075  Material Specification:  Qq-a-250/12, t6 federal specification single material response  Surface Treatment:  Oxide film
Aluminum alloy 7075  Material Specification:  Qq-a-250/12, t6 federal specification single material response  Surface Treatment:  Oxide film  Surface Treatment Specification:
Aluminum alloy 7075  Material Specification:  Qq-a-250/12, t6 federal specification single material response  Surface Treatment:  Oxide film  Surface Treatment Specification:  Mil-c-5541 military specification single treatment response
Aluminum alloy 7075  Material Specification: Qq-a-250/12, t6 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Mil-c-5541 military specification single treatment response Fsc Application Data:
Aluminum alloy 7075  Material Specification: Qq-a-250/12, t6 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Mil-c-5541 military specification single treatment response Fsc Application Data: Fuel tank, acft
Aluminum alloy 7075  Material Specification: Qq-a-250/12, t6 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Mil-c-5541 military specification single treatment response Fsc Application Data: Fuel tank, acft Shelf Life:
Aluminum alloy 7075  Material Specification: Qq-a-250/12, t6 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Mil-c-5541 military specification single treatment response Fsc Application Data: Fuel tank, acft Shelf Life: N/a
Aluminum alloy 7075  Material Specification: Qq-a-250/12, t6 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Mil-c-5541 military specification single treatment response Fsc Application Data: Fuel tank, acft Shelf Life: N/a
Aluminum alloy 7075  Material Specification: Qq-a-250/12, t6 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Mil-c-5541 military specification single treatment response Fsc Application Data: Fuel tank, acft Shelf Life: N/a Unit Of Measure:
Aluminum alloy 7075  Material Specification: Qq-a-250/12, t6 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Mil-c-5541 military specification single treatment response Fsc Application Data: Fuel tank, acft Shelf Life: N/a Unit Of Measure: Demilitarization:
Aluminum alloy 7075  Material Specification: Qq-a-250/12, t6 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Mil-c-5541 military specification single treatment response Fsc Application Data: Fuel tank, acft Shelf Life: N/a Unit Of Measure: Demilitarization: No
Aluminum alloy 7075  Material Specification: Qq-a-250/12, t6 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Mil-c-5541 military specification single treatment response Fsc Application Data: Fuel tank, acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: