## NSN 5340-00-886-6490

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-886-6490

Exprise tion Method (non coro).
Fabrication Method (non-core):
Stamped
First Leg Length:
1.062 inches
Second Leg Length:
2.125 inches
Reinforcement Method (non-core):
Web center section
Second Leg Width:
0.750 inches
First Leg Slot Length:
0.500 inches
First Leg Slot Width:
0.250 inches
Second Leg Hole Diameter:
0.098 inches
Second Leg Distance Between Hole Centers Along Width:
0.375 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
0.188 inches
Second Leg Distance Between Second And Third Hole Centers Along Width:
0.188 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.188 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.188 inches
Second Leg Distance Between First And Second Hole Centers Along Length:
0.188 inches
Second Leg Distance Between Second And Third Hole Centers Along Length:
0.188 inches
First Leg Thickness:
0.051 inches
Second Leg Thickness:
0.051 inches
Center Section Height:
0.625 inches
Center Section Width:
0.750 inches
Center Section Thickness:
0.051 inches
First Leg Width:
0.750 inches

## NSN 5340-00-886-6490

Double Angle Bracket - Page 2 of 2



First Leg Distance From Edge To Hole Center Along Width:
0.375 inches
First Leg Distance From Edge To Hole Center Along Length:
0.438 inches
First Leg End Radius:
0.500 inches
Second Leg End Radius:
0.500 inches
First Leg Style:
End radius
First Leg Hole Arrangement Style:
One slot
Second Leg Style:
End radius
Second Leg Hole Arrangement Style:
Four holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Material:
Aluminum alloy 2024
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0