

View Online at <https://aerobasegroup.com/nsn/5340-00-886-8529>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.880 inches and 0.920 inches

**Second Leg Corner Radius:**

Between 0.220 inches and 0.260 inches

**First Leg Slot Length:**

Between 0.480 inches and 0.520 inches

**First Leg Slot Width:**

Between 0.200 inches and 0.220 inches

**Second Leg Hole Diameter:**

0.281 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.360 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.380 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.220 inches and 0.260 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.220 inches and 0.260 inches

**First Leg Thickness:**

Between 0.073 inches and 0.083 inches

**Second Leg Thickness:**

Between 0.083 inches and 0.087 inches

**First Leg Corner Radius:**

Between 0.260 inches and 0.300 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.245 inches and 0.255 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.260 inches and 0.300 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Special Features:**

First leg angle in degrees 88.0 min. 92.0 max.

**Material:**

Steel comp 321

**Material Specification:**

Ams 5510 assn standard single material response

**Style Designator:**

Offset angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0