

View Online at <https://aerobasegroup.com/nsn/5340-00-886-8529>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.880 inches and 0.920 inches

Second Leg Corner Radius:

Between 0.220 inches and 0.260 inches

First Leg Slot Length:

Between 0.480 inches and 0.520 inches

First Leg Slot Width:

Between 0.200 inches and 0.220 inches

Second Leg Hole Diameter:

0.281 inches

Second Leg Distance Between Hole Centers Along Width:

1.360 inches

Second Leg Distance Between Hole Centers Along Length:

0.380 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.220 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.260 inches

First Leg Thickness:

Between 0.073 inches and 0.083 inches

Second Leg Thickness:

Between 0.083 inches and 0.087 inches

First Leg Corner Radius:

Between 0.260 inches and 0.300 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.245 inches and 0.255 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.260 inches and 0.300 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Special Features:

First leg angle in degrees 88.0 min. 92.0 max.

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Offset angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0