

View Online at <https://aerobasegroup.com/nsn/5340-00-888-2103>

First Leg Length:

Between 0.570 inches and 0.590 inches

Second Leg Length:

Between 0.570 inches and 0.590 inches

Second Leg Width:

Between 0.500 inches and 0.540 inches

First Leg Slot Length:

Between 0.300 inches and 0.320 inches

First Leg Slot Width:

Between 0.200 inches and 0.220 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.250 inches and 0.270 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.230 inches and 0.240 inches

Second Leg Slot Length:

Between 0.300 inches and 0.320 inches

Second Leg Slot Width:

Between 0.200 inches and 0.220 inches

First Leg Thickness:

Between 0.045 inches and 0.055 inches

Second Leg Thickness:

Between 0.045 inches and 0.053 inches

Center Section Height:

Between 0.525 inches and 0.555 inches

Center Section Width:

Between 0.500 inches and 0.540 inches

Center Section Thickness:

Between 0.045 inches and 0.055 inches

First Leg Width:

Between 0.500 inches and 0.540 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.250 inches and 0.270 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.230 inches and 0.240 inches

First Leg End Radius:

Between 0.450 inches and 0.550 inches

Second Leg End Radius:

Between 0.450 inches and 0.550 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Heat Treatment:

Tempered

Material:

Iron alloy 660

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0