NSN 5340-00-890-3401

Swivel Caster - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5340-00-690-3401 |
|---|
| Center To Center Distance Between Bolt Holes Along Width: |
| 6.125 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 4.125 inches |
| Wheel Quantity: |
| 2 |
| Tire Size: |
| 3.40/5 |
| Safe Operating Load Rating: |
| 1000.0 pounds |
| Material And Location: |
| Steel wheel rim err-100 err-100 |
| Surface Treatment And Location: |
| Paint wheel rim |
| Unpackaged Unit Weight: |
| 35.000 pounds |
| Wheel Type: |
| Pneumatic tire |
| Wheel Diameter: |
| 10.000 inches |
| Effective Height: |
| 13.000 inches |
| Features Provided: |
| Swivel lock |
| Plate Style: |
| Rectangular |
| Wheel Bearing Type: |
| Roller |
| Swivel Bearing Type: |
| Ball |
| Swivel Bearing Arrangement: |
| One row |
| Tread Width: |
| 3.500 inches |
| Caster Plate Length: |
| 7.250 inches |
| Caster Plate Width: |
| 5.250 inches |
| Caster Plate Mounting Hole Diameter: |
| 0.562 inches |

Swivel offset

Style Designator:

NSN 5340-00-890-3401

Swivel Caster - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A25600