NSN 5340-00-890-9224

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-890-9224

Fabrication Method (non-core):

Formed

First Leg Length:

Between 0.750 inches and 0.770 inches

Second Leg Length:

Between 0.750 inches and 0.770 inches

Second Leg Width:

Between 0.380 inches and 0.420 inches

First Leg Hole Diameter:

Between 0.220 inches and 0.240 inches

Second Leg Hole Diameter:

Between 0.220 inches and 0.240 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.190 inches and 0.210 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.190 inches and 0.210 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

Center Section Height:

Between 0.837 inches and 0.869 inches

Center Section Width:

Between 0.380 inches and 0.420 inches

Center Section Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 0.380 inches and 0.420 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.190 inches and 0.210 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.190 inches and 0.210 inches

First Leg End Radius:

Between 0.190 inches and 0.210 inches

Second Leg End Radius:

Between 0.190 inches and 0.210 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

NSN 5340-00-890-9224

Double Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:
One hole
Second Leg Relationship To First Leg:
Identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Material:
Steel comp 321
Material Specification:
Ams 5510 assn standard single material response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0