

View Online at <https://aerobasegroup.com/nsn/5340-00-893-4105>

**Center To Center Distance Between Bolt Holes Along Width:**

3.625 inches

**Center To Center Distance Between Bolt Holes Along Length:**

2.625 inches

**Wheel Quantity:**

1

**Safe Operating Load Rating:**

900.0 pounds

**Material And Location:**

Steel wheel rim err-100 err-100

**Surface Treatment And Location:**

Paint, aluminum wheel rim err-100 err-100

**Unpackaged Unit Weight:**

8.500 pounds

**Wheel Type:**

Pneumatic tire

**Wheel Diameter:**

5.000 inches

**Effective Height:**

6.625 inches

**Features Provided:**

Brake lock and axle lubrication fitting and swivel lubrication fitting

**Plate Style:**

Rectangular

**Wheel Bearing Type:**

Roller

**Swivel Bearing Type:**

Ball

**Swivel Bearing Arrangement:**

Two row

**King Bolt Bearing Type:**

Ball

**Tread Width:**

2.000 inches

**Caster Plate Length:**

4.750 inches

**Caster Plate Width:**

3.750 inches

**Caster Plate Mounting Hole Diameter:**

0.500 inches

**Style Designator:**

Swivel offset

**Reference Number Differentiating Characteristics:**

As differentiated by caster plate mounting hole diameter

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A25600