

View Online at <https://aerobasegroup.com/nsn/5340-00-893-5619>

**Thread Class:**

3b rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

0.625 inches rod connection

**Shank Length:**

Between 3.870 inches and 3.930 inches

**Hole Diameter:**

Between 0.275 inches and 0.282 inches

**Shank Diameter:**

Between 0.365 inches and 0.385 inches

**Overall Width:**

Between 0.428 inches and 0.448 inches

**End Radius:**

Between 0.280 inches and 0.340 inches

**Fork Span Width:**

Between 0.203 inches and 0.223 inches

**Securing Pin Hole Diameter:**

0.040 inches

**Distance From Center Of Securing Pin Hole To Rod End:**

Between 0.520 inches and 0.580 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

Between 4.740 inches and 4.800 inches

**Fork Arm Thickness:**

0.102 mils and 0.122 centimeters

**Fork Depth:**

0.062 inches

**Thread Size:**

0.250 inches rod connection

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758, cond d4 or f4 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

299-099-031, cb2, bell helicopter co mfr ref single treatment response

**Style Designator:**

Clevis

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A264a0

**Mil-std (military Standard):**

Mil-s-6758 spec.