

View Online at <https://aerobasegroup.com/nsn/5340-00-895-9345>

**Thread Class:**

2a rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

0.720 inches rod connection and 0.780 inches rod connection

**Shank Length:**

Between 1.530 inches and 1.650 inches

**Hole Diameter:**

Between 0.374 inches and 0.376 inches

**Shank Diameter:**

Between 0.672 inches and 0.682 inches

**Overall Width:**

Between 0.740 inches and 0.760 inches

**End Radius:**

0.500 inches

**Fork Span Width:**

Between 0.270 inches and 0.290 inches

**Distance From Center Of Securing Pin Hole To Rod End:**

2.300 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

Between 3.840 inches and 3.900 inches

**Fork Arm Thickness:**

0.235 inches

**Fork Depth:**

Between 1.870 inches and 1.930 inches

**Thread Size:**

0.750 inches rod connection

**Special Features:**

Item furnish w/1 setscrew

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758, cond d4 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

299-099-031, cc1, bell helicopter co mfr ref single treatment response

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A264a0

**Mil-std (military Standard):**

Mil-s-6758 spec.