

View Online at <https://aerobasegroup.com/nsn/5340-00-906-1326>

**Hole Diameter:**

Between 0.190 inches and 0.195 inches

**Width:**

Between 4.860 inches and 4.900 inches

**Edge Shape:**

Rectangle, multi holes

**Length:**

Between 8.780 inches and 8.820 inches

**Corner Radius:**

Between 0.290 inches and 0.330 inches

**Hole Quantity Along Length:**

4

**Hole Quantity Along Width:**

6

**Distance Between Holes Along Length:**

Between 2.484 inches and 2.504 inches

**Distance Between Holes Along Width:**

Between 2.010 inches and 2.030 inches

**Distance From First Hole Centerline To End Along Length:**

Between 0.640 inches and 0.680 inches

**Distance From First Hole Centerline To End Along Width:**

Between 0.410 inches and 0.430 inches

**Securing Device Type:**

Threaded fastener

**Mounting Opening Shape Style:**

Unthreaded hole

**Special Features:**

Waterproof to 5 ps1

**Material:**

Magnesium alloy az31b

**Material Specification:**

Qq-m-44, cond h24 federal specification single material response

**Surface Treatment:**

Dichromate

**Surface Treatment Specification:**

Mil-m-3171, type 3 military specification single treatment response

**Fsc Application Data:**

Fuselage sect., acft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A531c0

**Mil-std (military Standard):**

Mil-m-3171 spec.