

View Online at <https://aerobasegroup.com/nsn/5340-00-906-1326>

Hole Diameter:

Between 0.190 inches and 0.195 inches

Width:

Between 4.860 inches and 4.900 inches

Edge Shape:

Rectangle, multi holes

Length:

Between 8.780 inches and 8.820 inches

Corner Radius:

Between 0.290 inches and 0.330 inches

Hole Quantity Along Length:

4

Hole Quantity Along Width:

6

Distance Between Holes Along Length:

Between 2.484 inches and 2.504 inches

Distance Between Holes Along Width:

Between 2.010 inches and 2.030 inches

Distance From First Hole Centerline To End Along Length:

Between 0.640 inches and 0.680 inches

Distance From First Hole Centerline To End Along Width:

Between 0.410 inches and 0.430 inches

Securing Device Type:

Threaded fastener

Mounting Opening Shape Style:

Unthreaded hole

Special Features:

Waterproof to 5 ps1

Material:

Magnesium alloy az31b

Material Specification:

Qq-m-44, cond h24 federal specification single material response

Surface Treatment:

Dichromate

Surface Treatment Specification:

Mil-m-3171, type 3 military specification single treatment response

Fsc Application Data:

Fuselage sect., acft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A531c0

Mil-std (military Standard):

Mil-m-3171 spec.