NSN 5340-00-906-8054

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-906-8054

Fabrication Method (non-core):

Any acceptable

Mounting Hole Type:

Plain

First Leg Length:

Between 0.630 inches and 0.750 inches

Second Leg Length:

Between 3.490 inches and 3.550 inches

Second Leg Width:

1.380 inches

First Leg Hole Diameter:

Between 0.256 inches and 0.264 inches

Second Leg Hole Diameter:

Between 0.218 inches and 0.225 inches

Second Leg Distance Between Hole Centers Along Width:

0.625 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.755 inches

First Leg Thickness:

Between 0.022 inches and 0.042 inches

Second Leg Thickness:

Between 0.022 inches and 0.042 inches

First Leg Width:

Between 0.730 inches and 0.790 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.350 inches and 0.410 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.350 inches and 0.410 inches

First Leg End Radius:

Between 0.350 inches and 0.410 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

NSN 5340-00-906-8054

Angle Bracket - Page 2 of 2



| S | pe | cial | Fe | atui | es |
|---|----|------|----|------|----|
|---|----|------|----|------|----|

3 holes along Ig of second leg, 0.173 in. Dia, 0.500 in. Between each hole along Ig, 1.400 in. From edge to hole ctr

Material:

Steel comp 301

Material Specification:

Mil-s-5059 military specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-5059 spec.