

View Online at <https://aerobasegroup.com/nsn/5340-00-908-3231>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.625 inches

Second Leg Length:

0.875 inches

Second Leg Width:

0.500 inches

First Leg Slot Length:

0.237 inches

First Leg Slot Width:

0.195 inches

Second Leg Hole Diameter:

0.098 inches

Second Leg Distance Between Hole Centers Along Length:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.312 inches

First Leg Thickness:

0.100 inches

Second Leg Thickness:

0.100 inches

First Leg Width:

0.500 inches

First Leg Corner Radius:

0.085 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.167 inches

Second Leg End Radius:

0.188 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

95.0 degrees

Special Features:

Counterbore inside leg a 0.438 in. Dia. 0.040 in. Deepradius ends 0.085 in.

Heat Treatment:

Annealed

Material:

Steel comp 4130

Material Specification:

Mil-s-18729 military specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-s-18729 spec.