

View Online at <https://aerobasegroup.com/nsn/5340-00-911-4915>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.782 inches

Second Leg Length:

0.750 inches

Second Leg Width:

2.250 inches

Second Leg Corner Radius:

0.250 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Distance Between Hole Centers Along Width:

1.031 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.625 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.281 inches

First Leg Thickness:

0.051 inches

Second Leg Thickness:

0.051 inches

Center Section Height:

1.375 inches

Center Section Width:

2.250 inches

Center Section Thickness:

0.051 inches

First Leg Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Length:

0.313 inches

First Leg End Radius:

0.375 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, alclad t4 federal specification single material response

Surface Treatment:

Anodize and primer

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response and tt-p-1757 federal specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.