

View Online at <https://aerobasegroup.com/nsn/5340-00-911-9262>

Fabrication Method (non-core):

Stamped

First Leg Length:

Between 0.990 inches and 1.010 inches

Second Leg Length:

Between 1.360 inches and 1.380 inches

Second Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Hole Diameter:

Between 0.270 inches and 0.290 inches

Second Leg Hole Diameter:

Between 0.210 inches and 0.230 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

Between 0.038 inches and 0.048 inches

Second Leg Thickness:

Between 0.038 inches and 0.048 inches

First Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg End Radius:

Between 0.320 inches and 0.440 inches

Second Leg End Radius:

Between 0.320 inches and 0.440 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0