NSN 5340-00-916-8947

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-916-8947

| Cross | Sectional | Shape: |
|-------|-----------|--------|
|-------|-----------|--------|

Flat

Hole Diameter:

Between 0.181 inches and 0.195 inches

Width:

Between 5.734 inches and 5.766 inches

Edge Shape:

Rectangle, multi holes

Length:

Between 18.203 inches and 18.234 inches

Corner Radius:

Between 0.234 inches and 0.266 inches

Hole Quantity Along Length:

14

Hole Quantity Along Width:

_

Distance Between Holes Along Length:

Between 2.495 inches and 2.505 inches

Distance Between Holes Along Width:

Between 2.119 inches and 2.129 inches

Distance Between Hole Centerline And First Hole Along Length:

Between 1.370 inches and 1.380 inches

Distance Between Hole Centerline And First Hole Along Width:

Between 0.557 inches and 0.567 inches

Distance From First Hole Centerline To End Along Length:

Between 1.620 inches and 1.630 inches

Distance From First Hole Centerline To End Along Width:

Between 0.745 inches and 0.755 inches

Body Thickness:

Between 0.085 inches and 0.095 inches

Securing Device Type:

Threaded fastener

Mounting Opening Shape Style:

Unthreaded hole

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1, cl 1 military specification single treatment response

NSN 5340-00-916-8947

Access Cover - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A531c0 | |

Mil-std (military Standard):

Mil-a-8625 spec.

Shelf Life: