

View Online at <https://aerobasegroup.com/nsn/5340-00-918-0157>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.910 inches and 0.950 inches

Second Leg Length:

Between 1.617 inches and 1.647 inches

Second Leg Width:

Between 1.470 inches and 1.530 inches

Second Leg Corner Radius:

Between 0.200 inches and 0.300 inches

First Leg Hole Diameter:

0.265 inches

Second Leg Hole Diameter:

0.125 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.901 inches and 0.911 inches

Second Leg Distance Between Hole Centers Along Length:

Between 0.901 inches and 0.922 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.275 inches and 0.315 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.275 inches and 0.315 inches

First Leg Thickness:

Between 0.057 inches and 0.067 inches

Second Leg Thickness:

Between 0.057 inches and 0.067 inches

Center Section Height:

Between 0.970 inches and 1.030 inches

Center Section Width:

Between 1.470 inches and 1.530 inches

Center Section Thickness:

Between 0.057 inches and 0.067 inches

First Leg Width:

1.470 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.910 inches and 0.920 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.560 inches and 0.610 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.210 inches and 0.230 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0