NSN 5340-00-920-7761

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-920-7761

Fabrication Method (non-core):

Formed

First Leg Length:

Between 1.100 inches and 1.120 inches

Second Leg Length:

Between 1.100 inches and 1.120 inches

Second Leg Width:

Between 0.585 inches and 0.615 inches

First Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.290 inches and 0.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

Between 0.071 inches and 0.085 inches

Second Leg Thickness:

Between 0.071 inches and 0.085 inches

Center Section Height:

Between 1.990 inches and 2.010 inches

Center Section Width:

Between 0.585 inches and 0.615 inches

Center Section Thickness:

Between 0.071 inches and 0.085 inches

First Leg Width:

Between 0.585 inches and 0.615 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.290 inches and 0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg End Radius:

Between 0.469 inches and 0.531 inches

Second Leg End Radius:

Between 0.469 inches and 0.531 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

NSN 5340-00-920-7761Double Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:
One hole
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Material:
Steel comp 410
Material Specification:
Ams 5504 assn standard single material response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
N042a0