

View Online at <https://aerobasegroup.com/nsn/5340-00-922-1342>

Cross Sectional Shape:

Circular recess

Inside Diameter:

Between 1.677 inches and 1.697 inches

Hole Diameter:

Between 0.406 inches and 0.436 inches

Flange Thickness:

Between 0.115 inches and 0.135 inches

Outside Diameter:

Between 3.771 inches and 3.791 inches

Edge Shape:

Round, multi holes

Hole Quantity Along Length:

2

First Recess Inside Height:

Between 0.928 inches and 0.948 inches

Inside Corner Radius:

0.020 inches

Body Thickness:

Between 0.115 inches and 0.135 inches

Securing Device Type:

Threaded fastener

Mounting Opening Shape Style:

Unthreaded hole

Bolt Hole Centerline To Nearest Edge Distance:

0.453 inches

Distance Between Hole Centers:

2.875 inches

Material:

Zinc

Material Specification:

Mil-a-18001 military specification single material response

Surface Treatment:

Paint

Surface Treatment Specification:

Mil-std-1303, system no. 46a military standard single treatment response

Fsc Application Data:

Underwater mine anchor mk 56 mod 4, model no.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A531c0

Mil-std (military Standard):

Mil-a-18001 spec.