

View Online at <https://aerobasegroup.com/nsn/5340-00-922-1342>

**Cross Sectional Shape:**

Circular recess

**Inside Diameter:**

Between 1.677 inches and 1.697 inches

**Hole Diameter:**

Between 0.406 inches and 0.436 inches

**Flange Thickness:**

Between 0.115 inches and 0.135 inches

**Outside Diameter:**

Between 3.771 inches and 3.791 inches

**Edge Shape:**

Round, multi holes

**Hole Quantity Along Length:**

2

**First Recess Inside Height:**

Between 0.928 inches and 0.948 inches

**Inside Corner Radius:**

0.020 inches

**Body Thickness:**

Between 0.115 inches and 0.135 inches

**Securing Device Type:**

Threaded fastener

**Mounting Opening Shape Style:**

Unthreaded hole

**Bolt Hole Centerline To Nearest Edge Distance:**

0.453 inches

**Distance Between Hole Centers:**

2.875 inches

**Material:**

Zinc

**Material Specification:**

Mil-a-18001 military specification single material response

**Surface Treatment:**

Paint

**Surface Treatment Specification:**

Mil-std-1303, system no. 46a military standard single treatment response

**Fsc Application Data:**

Underwater mine anchor mk 56 mod 4, model no.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A531c0

**Mil-std (military Standard):**

Mil-a-18001 spec.