

View Online at <https://aerobasegroup.com/nsn/5340-00-922-3398>

Center To Center Distance Between Bolt Holes Along Width:

2.625 inches

Center To Center Distance Between Bolt Holes Along Length:

3.625 inches

Wheel Quantity:

1

Safe Operating Load Rating:

900.0 pounds

Material And Location:

Steel wheel rim err-100 err-100

Surface Treatment And Location:

Enamel, tt-e-529, class a wheel rim and enamel, tt-e-529, class a body and enamel, tt-e-529, class a plate or enamel, tt-e-529, class b wheel rim and enamel, tt-e-529, class b body and enamel, tt-e-529, class b plate

Unpackaged Unit Weight:

7.000 pounds

Wheel Type:

Built up

Wheel Diameter:

5.000 inches

Effective Height:

6.625 inches

Features Provided:

Axle lubrication fitting and spanner bushing

Plate Style:

Rectangular

Wheel Bearing Type:

Roller

Disassembly Capability:

Provided

Tread Width:

2.000 inches

Caster Plate Length:

4.750 inches

Caster Plate Width:

3.750 inches

Caster Plate Mounting Hole Diameter:

0.500 inches

Special Features:

Green, fed standard 595, no. 24300, over primer, mil-p-8565, color t

Style Designator:

Rigid

Reference Number Differentiating Characteristics:

As differentiated by the mounting hole diameter

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A25600