

View Online at <https://aerobasegroup.com/nsn/5340-00-922-3398>

**Center To Center Distance Between Bolt Holes Along Width:**

2.625 inches

**Center To Center Distance Between Bolt Holes Along Length:**

3.625 inches

**Wheel Quantity:**

1

**Safe Operating Load Rating:**

900.0 pounds

**Material And Location:**

Steel wheel rim err-100 err-100

**Surface Treatment And Location:**

Enamel, tt-e-529, class a wheel rim and enamel, tt-e-529, class a body and enamel, tt-e-529, class a plate or enamel, tt-e-529, class b wheel rim and enamel, tt-e-529, class b body and enamel, tt-e-529, class b plate

**Unpackaged Unit Weight:**

7.000 pounds

**Wheel Type:**

Built up

**Wheel Diameter:**

5.000 inches

**Effective Height:**

6.625 inches

**Features Provided:**

Axle lubrication fitting and spanner bushing

**Plate Style:**

Rectangular

**Wheel Bearing Type:**

Roller

**Disassembly Capability:**

Provided

**Tread Width:**

2.000 inches

**Caster Plate Length:**

4.750 inches

**Caster Plate Width:**

3.750 inches

**Caster Plate Mounting Hole Diameter:**

0.500 inches

**Special Features:**

Green, fed standard 595, no. 24300, over primer, mil-p-8565, color t

**Style Designator:**

Rigid

**Reference Number Differentiating Characteristics:**

As differentiated by the mounting hole diameter

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A25600