## NSN 5340-00-922-4318

Double Angle Bracket - Page 1 of 2

**Fabrication Method (non-core):** 



View Online at https://aerobasegroup.com/nsn/5340-00-922-4318

Machined
First Leg Length:
0.700 inches
Second Leg Length:
1.432 inches
Second Leg Width:
1.824 inches
Second Leg Corner Radius:
0.312 inches
First Leg Hole Diameter:
Between 0.214 inches and 0.224 inches
Second Leg Hole Diameter:
Between 0.214 inches and 0.224 inches
Second Leg Distance Between Lower Hole Centers Along Width:
1.200 inches
Second Leg Distance Between Hole Centers Along Length:
1.120 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
0.600 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.312 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.312 inches
First Leg Thickness:
Between 0.056 inches and 0.062 inches
Second Leg Thickness:
Between 0.056 inches and 0.062 inches
Center Section Height:
1.770 inches
Center Section Width:
0.500 inches
Center Section Thickness:
Between 0.056 inches and 0.062 inches
First Leg Width:
0.500 inches
First Leg Distance From Edge To Hole Center Along Width:
0.250 inches
First Leg Distance From Edge To Hole Center Along Length:
0.250 inches
First Leg End Radius:
0.250 inches

## NSN 5340-00-922-4318

Double Angle Bracket - Page 2 of 2



First Leg Style:
End radius
First Leg Hole Arrangement Style:
One hole
Second Leg Style:
Corner radius
Second Leg Hole Arrangement Style:
Three holes
Second Leg Relationship To First Leg:
Not identical
Second Leg Angle:
96.0 degrees
First Leg Offset Angle:
6.0 degrees
Second Leg Offset Angle:
6.0 degrees
Material:
Titanium alloy
Material Specification:
Ams4910 assn standard single material response
Style Designator:
Offset double angle
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiig:
A042a0