## NSN 5340-00-922-4336

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-922-4336

Fabrication Method (non-core):
Machined
First Leg Length:
0.750 inches
Second Leg Length:
1.460 inches
Second Leg Width:
2.700 inches
First Leg Hole Diameter:
Between 0.245 inches and 0.255 inches
First Leg Thickness:
Between 0.045 inches and 0.050 inches
Second Leg Thickness:
Between 0.045 inches and 0.050 inches
Center Section Height:
Between 0.881 inches and 0.886 inches
Center Section Width:
2.700 inches
Center Section Thickness:
Between 0.045 inches and 0.050 inches
First Leg Width:
2.700 inches
First Leg Corner Radius:
0.250 inches
First Leg Distance Between First And Second Hole Centers Along Width:
1.100 inches
First Leg Distance Between Second And Third Hole Centers Along Width:
1.100 inches
First Leg Distance From Edge To Hole Center Along Width:
0.250 inches
First Leg Distance From Edge To Hole Center Along Length:
0.250 inches
First Leg Style:
Corner radius
First Leg Hole Arrangement Style:
Three holes
Second Leg Style:
Square and tapered
Second Leg Hole Arrangement Style:
No hole
Second Leg Relationship To First Leg:

Not identical

## NSN 5340-00-922-4336

Double Angle Bracket - Page 2 of 2



Material:
Titanium alloy

**Material Specification:** 

Ams4910 assn standard single material response

**Style Designator:** 

Double angle

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0