

View Online at <https://aerobasegroup.com/nsn/5340-00-924-6348>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.490 inches

**Second Leg Length:**

2.720 inches

**End Application:**

ARMA-ME-NTS-UBSY

**Second Leg Width:**

3.850 inches

**First Leg Hole Diameter:**

0.180 inches

**Second Leg Hole Diameter:**

0.136 inches

**Second Leg Distance Between Hole Centers Along Width:**

3.400 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.350 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.230 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.900 inches

**First Leg Thickness:**

0.062 inches

**Second Leg Thickness:**

0.062 inches

**Center Section Height:**

3.320 inches

**Center Section Width:**

3.850 inches

**Center Section Thickness:**

0.062 inches

**First Leg Width:**

3.850 inches

**First Leg Distance Between Hole Centers Along Width:**

2.310 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.260 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.214 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Special Features:**

2nd leg bends to 0.580 in. Lg. By 3.850 in. W.; 2 holes 0.180 in. Dia.; center section has 4 holes 0.820 in. Dia. And 8 holes 0.160 in. Dia.

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type ii, class 2 military specification single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.