## NSN 5340-00-925-1279

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-925-1279 First Leg Length: 0.420 inches Second Leg Length: 0.710 inches Second Leg Width: 0.680 inches Second Leg End Width: 0.880 inches First Leg Hole Diameter: Between 0.124 inches and 0.126 inches Second Leg Hole Diameter: Between 0.142 inches and 0.149 inches Second Leg Distance Between Hole Centers Along Width: Between 0.485 inches and 0.505 inches Second Leg Distance Between Hole Centers Along Length: 0.042 mils and 0.044 centimeters Second Leg Distance From Edge To Hole Center Along Width: 0.215 inches Second Leg Distance From Edge To Hole Center Along Length: 0.170 inches First Leg Thickness: 0.040 inches Second Leg Thickness: 0.040 inches First Leg Width: 0.680 inches First Leg Distance Between Hole Centers Along Width: Between 0.340 inches and 0.350 inches First Leg Distance From Edge To Hole Center Along Width: 0.265 inches First Leg Distance From Edge To Hole Center Along Length: 0.170 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes **Second Leg Hole Arrangement Style:** Two holes Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

## NSN 5340-00-925-1279

Angle Bracket - Page 2 of 2



Special Features:
2nd leg has corners cut on 3 edges; nut, self lk, p/n 107b8160p11, 2 each included
Material:
Aluminum alloy
Material Specification:
Qq-a-318, h34 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type ii, dye black military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

A042a0

Mil-a-8625 spec.