

View Online at <https://aerobasegroup.com/nsn/5340-00-928-9699>

**First Leg Length:**

Between 0.922 inches and 0.952 inches

**Second Leg Length:**

Between 1.110 inches and 1.140 inches

**Second Leg Width:**

Between 1.485 inches and 1.515 inches

**First Leg Slot Length:**

Between 1.340 inches and 1.350 inches

**First Leg Slot Width:**

Between 1.260 inches and 1.270 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 1.235 inches and 1.265 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 1.235 inches and 1.265 inches

**Second Leg Slot Length:**

Between 1.278 inches and 1.288 inches

**Second Leg Slot Width:**

Between 1.200 inches and 1.210 inches

**First Leg Thickness:**

Between 1.056 inches and 1.068 inches

**Second Leg Thickness:**

Between 1.056 inches and 1.068 inches

**First Leg Width:**

Between 1.485 inches and 1.515 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 1.235 inches and 1.265 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 1.235 inches and 1.265 inches

**First Leg End Radius:**

Between 1.485 inches and 1.515 inches

**Second Leg End Radius:**

Between 1.485 inches and 1.515 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 321

**Material Specification:**

Ams 5510 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0