

View Online at <https://aerobasegroup.com/nsn/5340-00-928-9699>

First Leg Length:

Between 0.922 inches and 0.952 inches

Second Leg Length:

Between 1.110 inches and 1.140 inches

Second Leg Width:

Between 1.485 inches and 1.515 inches

First Leg Slot Length:

Between 1.340 inches and 1.350 inches

First Leg Slot Width:

Between 1.260 inches and 1.270 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 1.235 inches and 1.265 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 1.235 inches and 1.265 inches

Second Leg Slot Length:

Between 1.278 inches and 1.288 inches

Second Leg Slot Width:

Between 1.200 inches and 1.210 inches

First Leg Thickness:

Between 1.056 inches and 1.068 inches

Second Leg Thickness:

Between 1.056 inches and 1.068 inches

First Leg Width:

Between 1.485 inches and 1.515 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 1.235 inches and 1.265 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 1.235 inches and 1.265 inches

First Leg End Radius:

Between 1.485 inches and 1.515 inches

Second Leg End Radius:

Between 1.485 inches and 1.515 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0