

View Online at <https://aerobasegroup.com/nsn/5340-00-935-3944>

**Thread Class:**

3b rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

1.188 inches rod connection

**Radius:**

1.187 inches

**Overall Width:**

2.250 inches

**Metallic Hardness Rating:**

30.0 rockwell c and 35.0 rockwell c

**Shank Outside Diameter:**

1.500 inches

**Tongue Width:**

2.375 inches

**Tongue Thickness:**

0.654 inches

**Rod Connection Bore Diameter:**

1.000 inches

**Securing Pin Hole Diameter:**

0.187 inches

**Rod Connection Bore Depth:**

1.625 inches

**Distance From Center Of Securing Pin Hole To Rod End:**

0.500 inches

**Rod Connection End Length:**

1.188 inches

**Shanklength:**

0.750 inches

**Distance From End To Hole Center:**

3.188 inches

**Thread Size:**

1.000 inches rod connection

**Material:**

Steel comp 4140 or steel comp 8640 or steel comp 8740

**Material Specification:**

Sae assn standard single material response

**Surface Treatment:**

Phosphate zinc

**Surface Treatment Specification:**

Mil-p-16232, type z, class 3 military specification single treatment response

**Style Designator:**

Connector

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A264a0

**Mil-std (military Standard):**

Mil-p-16232 spec.