

View Online at <https://aerobasegroup.com/nsn/5340-00-935-8813>

**First Leg Length:**

Between 0.615 inches and 0.635 inches

**Second Leg Length:**

Between 0.990 inches and 1.010 inches

**Second Leg Width:**

Between 0.490 inches and 0.510 inches

**Second Leg Corner Radius:**

Between 0.240 inches and 0.260 inches

**First Leg Hole Diameter:**

Between 0.194 inches and 0.214 inches

**Second Leg Hole Diameter:**

Between 0.118 inches and 0.138 inches

**Second Leg Distance Between Hole Centers Along Length:**

Between 0.365 inches and 0.385 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.260 inches

**First Leg Thickness:**

Between 0.040 inches and 0.060 inches

**Second Leg Thickness:**

Between 0.040 inches and 0.060 inches

**First Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.260 inches

**First Leg End Radius:**

Between 0.240 inches and 0.260 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/5, alclad t3 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 1 or type 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.