

View Online at <https://aerobasegroup.com/nsn/5340-00-935-8823>

**First Leg Length:**

0.812 inches

**Second Leg Length:**

2.062 inches

**Reinforcement Method (non-core):**

Web both sides

**Second Leg Width:**

0.750 inches

**First Leg Slot Length:**

0.500 inches

**First Leg Slot Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.375 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.437 inches

**Second Leg Slot Length:**

0.500 inches

**Second Leg Slot Width:**

0.250 inches

**First Leg Thickness:**

0.040 inches

**Second Leg Thickness:**

0.040 inches

**First Leg Width:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.375 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.312 inches

**First Leg End Radius:**

0.500 inches

**Second Leg End Radius:**

0.500 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 302

**Material Specification:**

Mil-s-5059, cond a military specification single material response

**Surface Treatment:**

Passivate

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-s-5059 spec.