

View Online at <https://aerobasegroup.com/nsn/5340-00-937-3139>

Fabrication Method (non-core):

Stamped

First Leg Length:

Between 1.100 inches and 1.140 inches

Second Leg Length:

Between 0.800 inches and 0.840 inches

Second Leg Width:

Between 0.740 inches and 0.760 inches

First Leg Hole Diameter:

Between 0.157 inches and 0.164 inches

Second Leg Hole Diameter:

Between 0.435 inches and 0.443 inches

Second Leg Distance Between Hole Centers Along Length:

0.480 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.400 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.170 inches

First Leg Thickness:

Between 0.038 inches and 0.058 inches

Second Leg Thickness:

Between 0.038 inches and 0.058 inches

First Leg Width:

Between 0.740 inches and 0.760 inches

First Leg Distance Between Hole Centers Along Length:

0.360 inches

First Leg Distance From Edge To Hole Center Along Width:

0.400 inches

First Leg Distance From Edge To Hole Center Along Length:

0.170 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 1008 or steel comp 1009 or steel comp 1015 or steel comp 1018 or steel comp 1020

Material Specification:

Astm a109 assn standard 1st material response or astm a611 assn standard 2nd material response or astm a635 assn standard 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl2 federal specification all treatment responses

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0