

View Online at <https://aerobasegroup.com/nsn/5340-00-937-3139>

**Fabrication Method (non-core):**

Stamped

**First Leg Length:**

Between 1.100 inches and 1.140 inches

**Second Leg Length:**

Between 0.800 inches and 0.840 inches

**Second Leg Width:**

Between 0.740 inches and 0.760 inches

**First Leg Hole Diameter:**

Between 0.157 inches and 0.164 inches

**Second Leg Hole Diameter:**

Between 0.435 inches and 0.443 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.480 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.400 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.170 inches

**First Leg Thickness:**

Between 0.038 inches and 0.058 inches

**Second Leg Thickness:**

Between 0.038 inches and 0.058 inches

**First Leg Width:**

Between 0.740 inches and 0.760 inches

**First Leg Distance Between Hole Centers Along Length:**

0.360 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.400 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.170 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 1008 or steel comp 1009 or steel comp 1015 or steel comp 1018 or steel comp 1020

**Material Specification:**

Astm a109 assn standard 1st material response or astm a611 assn standard 2nd material response or astm a635 assn standard 3rd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl2 federal specification all treatment responses

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0