

View Online at <https://aerobasegroup.com/nsn/5340-00-938-0547>

Mounting Hole Type:

Countersunk

First Leg Length:

Between 2.490 inches and 2.510 inches

Second Leg Length:

Between 14.870 inches and 14.890 inches

Second Leg Width:

Between 1.210 inches and 1.990 inches

Second Leg Corner Radius:

Between 0.240 inches and 0.260 inches

First Leg Hole Diameter:

Between 0.271 inches and 0.291 inches

Second Leg Hole Diameter:

Between 0.177 inches and 0.197 inches

Second Leg Distance Between Upper Hole Centers Along Width:

1.950 inches

Second Leg Distance Between Hole Centers Along Length:

1.310 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

1.030 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.270 inches and 0.290 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.300 inches and 0.360 inches

First Leg Thickness:

Between 0.240 inches and 0.260 inches

Second Leg Thickness:

Between 0.240 inches and 0.260 inches

First Leg Width:

Between 1.990 inches and 2.010 inches

First Leg Corner Radius:

Between 0.240 inches and 0.260 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.990 inches and 1.010 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.271 inches and 0.291 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 1.200 inches and 1.240 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 1020

Surface Treatment:

Oxide

Surface Treatment Specification:

Ams 2485 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0