

View Online at <https://aerobasegroup.com/nsn/5340-00-938-0547>

**Mounting Hole Type:**

Countersunk

**First Leg Length:**

Between 2.490 inches and 2.510 inches

**Second Leg Length:**

Between 14.870 inches and 14.890 inches

**Second Leg Width:**

Between 1.210 inches and 1.990 inches

**Second Leg Corner Radius:**

Between 0.240 inches and 0.260 inches

**First Leg Hole Diameter:**

Between 0.271 inches and 0.291 inches

**Second Leg Hole Diameter:**

Between 0.177 inches and 0.197 inches

**Second Leg Distance Between Upper Hole Centers Along Width:**

1.950 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.310 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

1.030 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.270 inches and 0.290 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.300 inches and 0.360 inches

**First Leg Thickness:**

Between 0.240 inches and 0.260 inches

**Second Leg Thickness:**

Between 0.240 inches and 0.260 inches

**First Leg Width:**

Between 1.990 inches and 2.010 inches

**First Leg Corner Radius:**

Between 0.240 inches and 0.260 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 0.990 inches and 1.010 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.271 inches and 0.291 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 1.200 inches and 1.240 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 1020

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Ams 2485 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0