

View Online at <https://aerobasegroup.com/nsn/5340-00-941-0205>

**Thread Class:**

3b rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

0.800 inches rod connection

**Hole Diameter:**

Between 0.251 inches and 0.253 inches

**Shank Diameter:**

Between 0.365 inches and 0.385 inches

**Overall Width:**

Between 0.540 inches and 0.560 inches

**End Radius:**

Between 0.185 inches and 0.195 inches

**Metallic Hardness Rating:**

25.0 rockwell c and 33.0 rockwell c

**Fork Span Width:**

Between 0.345 inches and 0.347 inches

**Securing Pin Hole Diameter:**

Between 0.060 inches and 0.080 inches

**Distance From Center Of Securing Pin Hole To Rod End:**

0.280 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

Between 2.190 inches and 2.210 inches

**Fork Arm Thickness:**

0.156 inches

**Fork Depth:**

Between 1.090 inches and 1.110 inches

**Distance From Pivot Pinhole Center To Fork End:**

0.205 inches

**Thread Size:**

0.250 inches rod connection

**Material:**

Steel comp 410

**Material Specification:**

Ams 5613 assn standard single material response

**Surface Treatment:**

Passivate

**Style Designator:**

Clevis

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A264a0