

View Online at <https://aerobasegroup.com/nsn/5340-00-950-1392>

Center To Center Distance Between Bolt Holes Along Width:

Between 6.990 inches and 7.010 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 9.740 inches and 9.760 inches

Wheel Quantity:

1

Tire Size:

4.00-8

Safe Operating Load Rating:

950.0 pounds

Material And Location:

Rubber, soft tread err-100 err-100

Surface Treatment And Location:

Any acceptable

Wheel Type:

Pneumatic tire

Wheel Diameter:

16.000 inches

Effective Height:

Between 20.375 inches and 20.625 inches

Features Provided:

Axle lubrication fitting and swivel lock and swivel lubrication fitting

Plate Style:

Rectangular

Wheel Bearing Type:

Roller or tapered roller

Swivel Bearing Type:

Ball or roller or tapered roller

Swivel Bearing Arrangement:

Two row

Tread Width:

4.000 inches

Caster Plate Length:

11.000 inches

Caster Plate Width:

9.000 inches

Caster Plate Mounting Hole Diameter:

Between 0.652 inches and 0.660 inches

Style Designator:

Swivel offset

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A25600