NSN 5340-00-955-1590

Angle Bracket - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5340-00-955-1590 |
|---|
| Fabrication Method (non-core): Machined |
| First Leg Length: |
| Between 1.530 inches and 1.610 inches |
| Second Leg Length: |
| Between 2.070 inches and 2.150 inches |
| Second Leg Width: |
| Between 2.280 inches and 2.360 inches |
| Second Leg Corner Radius: |
| Between 0.300 inches and 0.340 inches |
| First Leg Hole Diameter: |
| 0.281 inches |
| First Leg Thickness: |
| Between 0.082 inches and 0.098 inches |
| Second Leg Thickness: |
| Between 0.082 inches and 0.098 inches |
| First Leg Width: |
| Between 3.150 inches and 3.190 inches |
| First Leg Corner Radius: |
| Between 0.250 inches and 0.270 inches |
| First Leg Distance Between Hole Centers Along Width: |
| 2.650 inches |
| First Leg Distance From Edge To Hole Center Along Width: |
| Between 0.250 inches and 0.270 inches |
| First Leg Distance From Edge To Hole Center Along Length: |
| Between 0.250 inches and 0.270 inches |
| First Leg Style: |
| Corner radius |
| First Leg Hole Arrangement Style: |
| Two holes |
| Second Leg Style: |
| Corner radius |
| First Leg Angle: |
| 90.0 degrees |
| Material: |
| Steel comp 321 |
| Material Specification: |
| Ams 5510 assn standard single material response |
| Style Designator: |
| Angle |

Shelf Life:

N/a

NSN 5340-00-955-1590 Angle Bracket - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV | еа | SU | ıre: |

Demilitarization:

No

Fiig:

A042a0