

View Online at <https://aerobasegroup.com/nsn/5340-00-957-3530>

Fabrication Method (non-core):

Machined

First Leg Length:

1.030 inches

Second Leg Length:

1.125 inches

Second Leg Width:

3.600 inches

Second Leg Corner Radius:

0.375 inches

First Leg Hole Diameter:

Between 0.255 inches and 0.265 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

3.600 inches

First Leg Distance Between Hole Centers Along Width:

Between 2.840 inches and 2.844 inches

First Leg Distance From Edge To Hole Center Along Width:

0.380 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.375 inches and 0.380 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

No hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel

Material Specification:

Ams 6382 assn standard single material response

Nuclear Hardness Critical Feature:

Hardened

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 3, class 2 federal specification single treatment response

Style Designator:

Angle

Fsc Application Data:

Launcher, guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0