

View Online at <https://aerobasegroup.com/nsn/5340-00-957-3530>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

1.030 inches

**Second Leg Length:**

1.125 inches

**Second Leg Width:**

3.600 inches

**Second Leg Corner Radius:**

0.375 inches

**First Leg Hole Diameter:**

Between 0.255 inches and 0.265 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

3.600 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 2.840 inches and 2.844 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.380 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.375 inches and 0.380 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

No hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel

**Material Specification:**

Ams 6382 assn standard single material response

**Nuclear Hardness Critical Feature:**

Hardened

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 3, class 2 federal specification single treatment response

**Style Designator:**

Angle

**Fsc Application Data:**

Launcher, guided missile

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0