

View Online at <https://aerobasegroup.com/nsn/5340-00-962-1011>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.910 inches and 0.930 inches

**Second Leg Length:**

Between 0.240 inches and 0.260 inches

**Second Leg Width:**

Between 0.760 inches and 0.780 inches

**First Leg Slot Length:**

Between 0.480 inches and 0.520 inches

**First Leg Slot Width:**

Between 0.260 inches and 0.280 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.380 inches and 0.390 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.510 inches and 0.570 inches

**Second Leg Slot Length:**

Between 0.480 inches and 0.520 inches

**Second Leg Slot Width:**

Between 0.210 inches and 0.230 inches

**First Leg Thickness:**

0.090 inches

**Second Leg Thickness:**

0.090 inches

**First Leg Width:**

Between 0.760 inches and 0.780 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.380 inches and 0.390 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.320 inches and 0.380 inches

**First Leg End Radius:**

Between 0.390 inches and 0.410 inches

**Second Leg End Radius:**

0.420 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 321

**Material Specification:**

Ams 5510 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0