

View Online at <https://aerobasegroup.com/nsn/5340-00-962-1011>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.910 inches and 0.930 inches

Second Leg Length:

Between 0.240 inches and 0.260 inches

Second Leg Width:

Between 0.760 inches and 0.780 inches

First Leg Slot Length:

Between 0.480 inches and 0.520 inches

First Leg Slot Width:

Between 0.260 inches and 0.280 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.380 inches and 0.390 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.510 inches and 0.570 inches

Second Leg Slot Length:

Between 0.480 inches and 0.520 inches

Second Leg Slot Width:

Between 0.210 inches and 0.230 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

Between 0.760 inches and 0.780 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.380 inches and 0.390 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.320 inches and 0.380 inches

First Leg End Radius:

Between 0.390 inches and 0.410 inches

Second Leg End Radius:

0.420 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0