## NSN 5340-00-973-8632

Rigid Caster - Page 1 of 2



## Center To Center Distance Between Bolt Holes Along Width:

3.375 inches

## Center To Center Distance Between Bolt Holes Along Length:

5.250 inches

## Wheel Quantity:

1

## Tire Size:

4.10/3.50-6

## Safe Operating Load Rating:

650.0 pounds

## Material And Location:

Steel, aisi c1045 plate err-100 err-100

## **Surface Treatment And Location:**

Enamel, green wheel rim err-100 err-100

## Unpackaged Unit Weight:

18.250 pounds

## Wheel Type:

Pneumatic tire

## Wheel Diameter:

13.000 inches

## Effective Height:

14.000 inches

## Plate Style:

Rectangular

## Wheel Bearing Type:

Annular ball

## **Disassembly Capability:**

Provided

## Tread Width:

3.375 inches

## **Caster Plate Length:**

6.500 inches

## **Caster Plate Width:**

5.000 inches

## **Caster Plate Mounting Hole Diameter:**

0.500 inches

## Style Designator:

Rigid

## Shelf Life:

N/a

## Unit Of Measure:

---



# NSN 5340-00-973-8632

Rigid Caster - Page 2 of 2

Demilitarization:

No

Fiig:

A25600

