NSN 5340-00-977-0868

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-977-0868 **Fabrication Method (non-core):** Machined First Leg Length: 2.000 inches Second Leg Length: 1.500 inches Second Leg Width: Between 2.160 inches and 2.222 inches First Leg Hole Diameter: Between 0.740 inches and 0.760 inches Second Leg Hole Diameter: Between 0.280 inches and 0.286 inches Second Leg Distance Between Hole Centers Along Width: Between 1.505 inches and 1.515 inches Second Leg Distance From Edge To Hole Center Along Width: Between 0.330 inches and 0.350 inches **Second Leg Distance From Edge To Hole Center Along Length:** Between 0.730 inches and 0.770 inches First Leg Thickness: 0.250 inches Second Leg Thickness: 0.250 inches First Leg Width: Between 2.160 inches and 2.220 inches First Leg Distance From Edge To Hole Center Along Width: Between 1.080 inches and 1.120 inches First Leg Distance From Edge To Hole Center Along Length: Between 1.020 inches and 1.030 inches First Leg Style: Square First Leg Hole Arrangement Style: One hole Second Leg Style: Square Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees

Steel

Material:

NSN 5340-00-977-0868 Angle Bracket - Page 2 of 2

Fiig: A042a0



| Material Specification: |
|---|
| 66, aisi/sae 1020 federal standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 1, class 1 federal specification single treatment response |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |