## NSN 5340-00-987-2221

Angle Bracket - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5340-00-987-2221  |
|--|
| First Leg Length:  |
| Between 0.743 inches and 0.755 inches  |
| Second Leg Length:   |
| Between 0.807 inches and 0.817 inches  |
| First Leg Hole Diameter:   |
| Between 0.214 inches and 0.224 inches  |
| First Leg Thickness:   |
| Between 0.054 inches and 0.064 inches  |
| Second Leg Thickness:  |
| Between 0.054 inches and 0.064 inches  |
| First Leg Width:   |
| 0.500 inches   |
| First Leg Distance From Edge To Hole Center Along Width:   |
| 0.250 inches   |
| First Leg Distance From Edge To Hole Center Along Length:  |
| Between 0.495 inches and 0.505 inches  |
| First Leg Style:   |
| End radius   |
| First Leg Hole Arrangement Style:  |
| One hole   |
| Second Leg Relationship To First Leg:  |
| Not identical  |
| First Leg Angle:   |
| 90.0 degrees   |
| Material:  |
| Steel comp 4130 or steel comp 8630   |
| Material Specification:  |
| $Ams\ 6350\ assn\ standard\ 1st\ material\ response\ or\ ams\ 6355\ assn\ standard\ 2nd\ material\ response$ |
| Surface Treatment:   |
| Cadmium  |
| Surface Treatment Specification:   |
| Ams 2400 assn standard single treatment response   |
| Style Designator:  |
| Angle  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |

Fiig:

A042a0